

211284 Part# OIL DRI  
 OIL ABSORBENT, 40-LB. #ST-1035  
 0556000 LOUIS O. BEEDE & SONS, II  
 Buyer: Charles H. Aubuchon

MATERIAL SAFETY DATA SHEET  
 (Similar to OSHA Form 174)

SECTION I -- IDENTIFICATION

<u>IDENTITY</u> OIL-DRI® FLOOR ABSORBENT	<u>EMERGENCY TELEPHONE</u> 800-621-7191
<u>CHEMICAL FAMILY</u> Fullers Earth	<u>INFORMATION TELEPHONE</u> 312-321-1515
<u>MANUFACTURER'S NAME</u> Oil-Dri Corporation of America	
<u>ADDRESS</u> 520 North Michigan Avenue Chicago, Illinois 60611	<u>DATE PREPARED</u>
<u>CAS NO.</u> 8031-18-3	
<u>D.O.T. CLASSIFICATION</u> Not regulated	

SECTION II -- HAZARDOUS INGREDIENTS OF MIXTURES

Mineral particulates are classified as nuisance dusts by the American Conference of Governmental Industrial Hygienists (ACGIH). This material may contain approximately 3% quartz. Use ACGIH publication to determine appropriate TLV. Applications data show concentrations well below TLV with normal use.

SECTION III -- PHYSICAL/CHEMICAL CHARACTERISTICS

<u>BOILING POINT</u> Not applicable (N/A)	<u>SPECIFIC GRAVITY</u> (H <sub>2</sub> O = 1) 2.2
<u>VAPOR PRESSURE</u> (mmHg) (N/A)	<u>MELTING POINT</u> N/A
<u>VAPOR DENSITY</u> (Air = 1) (N/A)	<u>EVAPORATION RATE</u> (Butyl Acetate = 1) (N/A)
<u>SOLUBILITY IN WATER</u> Insoluble	<u>APPEARANCE AND ODOR</u> Grey to Tan, Odorless

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

This material poses no fire or explosion hazard.

The information in this data sheet is believed to be accurate. However, user should make its own test to determine the suitability of the product for its purpose. OIL-DRI CORPORATION OF AMERICA MAKES NO WARRANTY EXPRESS OR IMPLIED WITH RESPECT TO THE PRODUCT and assumes no responsibility for any loss or liability arising from use of the information or the product. Statements about the product should not be construed as recommendations to use the product in infringement of any patent.

---

SECTION V -- REACTIVITY DATA

---

STABILITY Stable

INCOMPATABILITY Contact with turpentine, vegetable oil and other unsaturated organic compounds and with hydrofluoric acid may generate heat.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS None

HAZARDOUS POLYMERIZATION Will not occur

---

SECTION VI -- HEALTH HAZARD DATA

---

INHALATION Nuisance Dust

HEALTH HAZARDS Repeated inhalation of excessive concentrations of any dust, including this material, may lead to lung injury.

CARCINOGENICITY None

SIGNS AND SYMPTOMS OF EXPOSURE N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE N/A

EMERGENCY AND FIRST AID PROCEDURES N/A

---

SECTION VII -- PRECAUTIONS FOR SAFE HANDLING OR USE

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Vacuum or scoop up

WASTE DISPOSAL METHOD Unused material may be disposed of in sanitary landfills. Check with appropriate regulatory authority for used material containing hazardous waste.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE None

OTHER PROCEDURES N/A

---

SECTION VIII -- CONTROL MEASURES

---

RESPIRATORY PROTECTION Dust respirator in compliance with NIOSH

VENTILATION Local exhaust

PROTECTIVE GLOVES N/A

OTHER PROTECTIVE CLOTHING OR EQUIPMENT N/A

WORK/HYGENIC PRACTICES Normal good work practices